



SmartFind S5A AIS SART

The SmartFind S5A AIS SART is a manual deployment survival craft AIS Search and Rescue Transmitter (AIS SART), intended for use on life rafts or survival craft. It meets IMO SOLAS requirements and is a replacement for legacy radar SARTs.



SmartFind S5A AIS SART

Compact and easy to both operate and deploy, the SmartFind S5A AIS SART is packed inside a quick release carry off bag, that allows a survival crafts location to be identified by rescue authorities and nearby AIS equipped vessels.

The SmartFind S5A transmits target survivor craft information, including structured alert messages, GNSS position information and serialised identity number. Once activated the SmartFind S5A AIS SART transmits continually for a minimum of 96 hours. An inbuilt high precision GNSS receiver provides accurate position information to assist in the detection of the survival crafts' location.

Whether wall mounted in the ships bridge or packed inside a survival craft, the highly visible and buoyant carry case affords maximum protection.

- Internationally approved
- Ship or Survival craft options
- Waterproof to 10m
- Buoyant/floats
- Rugged, compact and lightweight
- Minimum 96 hour operational battery life
- 6 year battery life
- Visual indication of operation
- Built-in test facility
- Mounting options – Internal/External
- Transmits GNSS coordinates
- Interoperability with AIS Users
- Telescopic Mounting Pole included
- Comes with protective carry off bag

Technical Specifications

Beacon Specification Standards applied

APPLICABLE STANDARDS	IEC 61097-14 Ed.1 (2010) IEC 60945 Ed. 4 (2002) incl. Corrigendum 1 (2008) IMO Resolution A.694 (17) IMO Resolution MSC.246 (83) IMO Res. MSC.302 (87)* ITU-R M.1371-5 (2014) *: This covers Bridge Alert Management and it is not applicable for AIS	
VHF TRANSMITTER	Operating Frequency	AIS 1, 161.975MHz AIS 2, 162.025MHz
	Data Rate	9,600bps
	Bandwidth	25 KHz
	Power Output	1W EIRP
	AIS Message Type	Message 1, Message 14
	Modulation	GMSK
	Antenna	Integrated by PCB
GNSS RECEIVER	Receiving Channels	48 channels
	Acquisition Sensitivity	(-)-159 dBm
	Tracking Sensitivity	(-)-159 dBm
	Position Accuracy	< 2.5 m Autonomous & SBAS
BATTERY	Type	Primary Lithium (not rechargeable)
	Operating Life	96 hours minimum
	Storage	6 years
	Service	Replaceable
CARRY & MOUNTING	Carry Bag	
	Wall Mount	

ENVIRONMENT	Operating temperature Storage temperature Waterproof Buoyancy Exterior Finish Compass safe distance	-20°C to +55°C -30°C to +70°C Immersion to 10m Floats Highly visible Yellow Standard Magnetic – 0.60m Steering Magnetic – 0.40m
PHYSICAL	Max Diameter (Main Body) Length (Main Body) Weight (Main Body) Length (Pole) Weight (Pole) Total Weight (Storage Package)	70 mm 300 mm 283g (Battery included) 1050mm (Extended) 300g 1.08kg

